

RMS pumptools

SPEEDFIT

Field Attachable
for Wellhead and
Packer Penetrators



performance with reliability

SPEEDFIT - Field Attachable for Wellhead and Packer Penetrators

Less than 10 Minutes Assembly Time in the Field after the Cable is Stripped

RMSpumptools *SPEEDFIT* is the new benchmark for high-speed, consistently reliable field installations of downhole cable to wellhead and packer penetrators - saving you even more rig time. Requiring minimal parts and training, just a cable prep is required - *SPEEDFIT* requires no tapes, no epoxy, no gel and no assembly of parts.



SPEEDFIT Specs...

- Pressure Rating: 5000psi working, 7500psi test
- Temperature Rating: 150°C (302°F)
- Power Rating: Up to 160 Amps 5kVAC
- Min ID Wellhead Profile: Ø2"
- Max OD Coupling Nut: Ø2.25"
- Plug and Play Style Assembly
- Dual Sealing - retains the exclusive Field Proven RMSpumptools Pressure Barrier
- Back-up O-Ring Seals between Field Attachable Connector and Penetrators.
- Fully testable after being installed on the Cable.
- Suits a range of Cable Sizes.



SPEEDFIT is easily adaptable for use with different size cables, resulting in simple redress for re-use with only a minimum of spares required. The Vertical Penetrator can be installed top or bottom fed into the Tubing Hanger, allowing simple retrofit to existing wellhead equipment designs.

SPEEDFIT - 3 Stage Guide to Simple Installation**STAGE 1**

Strip the cable and crimp the contacts.

**STAGE 2**

Insert the cable into the housing and secure the nuts from the front.

**STAGE 3**

Tighten the threads on the body to energise the seals.



Various Redress Options available including:

- Boot Sizes
- Contact Sizes
- Cable Gland Sizes
(to suit both flat and round cable options)

All that is needed for redress kits are two seals and new pins.

No tapes, no epoxy, no gel and no assembly of parts - the new RMSpumptools Field Attachable