Proportional pressure reducing valve
Screw-in cartridge
- **Pilot operated**
- **Q_{max} = 60 l/min**
- **p_{max} = 400 bar**
- **$p_{N\ red\ max}$ = 350 bar**

$^{7}/_{8}$"-14 UNF
Wandfluh-Norm



DESCRIPTION
Pilot operated proportional pressure reducing valve as a screw-in cartridge with a thread 7/8"-14 UNF for cavity according to Wandfluh standard. Seven standard pressure levels are available. The adjustment takes place by means of a Wandfluh proportional solenoid (VDE-standard 0580). The cartridge body made of steel is zinc coated and therefore rust-protected. The solenoid coil is zinc-/ nickel-coated.

FUNCTION
The proportional pressure regulating valve controls the pressure in port A (1). Proportionally to the solenoid current solenoid force and pressure in port A (1) rise. The valve functions practically independently of pressure in port P (2). A pressure rise in Port A (1) above the set pressure, e.g. due to an active oil consumer, will be prevented by reliefing excess volume flow to tank via port T (3). With deneergised solenoid the volume flow passes freely from port P to the consumer port A. Thereby, because of the system, a minimum adjustable pressure in accordance with the characteristic curve cannot be fallen short of. To control the valve, proportional amplifiers are available from Wandfluh (see register 1.13).

APPLICATION
The valve has its application in hydraulic systems, in which the pressure frequently has to be changed. The facility for electric remote controlling of the valve in conjunction with process control systems enables economic problem solutions with repeatable sequences. Installation of the screw-in cartridge in control blocks.

TYPE CODE

M V P PU10 - [ ] - [ ] / [ ] [ ] - [ ] [ ] # [ ]

Pressure reducing valve					
Pilot operated					
Proportional					
Screw-in thread 7/8"-14 UNF					
Standard nominal pressure range $p_{N\,red}$	20 bar	20	200 bar	200	
	63 bar	63	275 bar	275	
	100 bar	100	350 bar	350	
	160 bar	160			
Standard nominal voltage U_N	12 VDC	G12			
	24 VDC	G24			
	without solenoid coil	X5			
Slip-on coil	Metal housing, round	W			
	Metal housing, square	M*			
Electric connection	Connector socket EN 175301-803 / ISO 4400	D			
	Connector socket AMP Junior-Timer	J			
	Connector Deutsch DT04-2P	G			
Sealing material	NBR				
	FKM (Viton)	D1			
Manual override	Armature tube closed (standard)				
	With screwed sealing plug	HB0			
	With manual emergency actuation	HB4.5			
Design-Index (Subject to change)					

• Only available in conjunction with other nominal voltages and connection versions. (See data sheet 1.1-174)

SYMBOLS



GENERAL SPECIFICATIONS

Denomination	Pilot operated proportional pressure reducing valve
Construction	Screw-in cartridge for cavity acc. to Wandfluh standard
Actuation	Proportional solenoid
Mounting	Screw in thread 7/8"-14 UNF
Ambient temperature	-20…70 °C
Mounting position	any, preferably horizontal
Fastening torque	M_D = 50 Nm for screw-in cartridge M_D = 5 Nm for knurled nut
Weight	m = 0,53 kg

ELECTRICAL SPECIFICATIONS

Construction	Proportional solenoid, wet pin push type, pressure tight	
Standard nominal voltage	U_N = 12 VDC	U_N = 24 VDC
Limiting current	I_G = 1320 mA	I_G = 660 mA
Relative duty factor	100% ED / DF (see data sheet 1.1-430)	
Protection class acc. to EN 60529	Connection version D: IP 65 J: IP 66 G: IP 67 and 69 K	

For further electrical specifications see data sheet 1.1-173 (W)
1.1-174 (M)

HYDRAULIC SPECIFICATIONS

Fluid	Mineral oil, other fluid on request
Contamination efficiency	ISO 4406: 1999, class 18/16/13 (Required filtration grade ß 6…10≥75) refer to data sheet 1.0-50/2
Viscosity range	12 mm²/s…320 mm²/s
Fluid temperature	-20…+70 °C
Peak pressure	p_{max} = 400 bar
Nominal pressure range:	$p_{N\,red}$ = 20 bar, 63 bar,100 bar,160 bar, 200 bar, 275 bar, 350 bar
Volume flow range	Q = 0…60 l/min
Pilot- and leakage volume flow	see characteristics
Repeatability	≤ 1% *
Hysteresis	≤ 4% *
	* at optimal dither signal

CHARACTERISTICS Oil viscosity υ = 30 mm²/s

p_{red} = f (Q) Pressure volume flow characteristics (Maximal adjustable pressure)



p_{red} = f (Q) Pressure volume flow characteristics (Minimal adjustable pressure)

* Consumption resistance dependent on system



p_{red} = f (I) Pressure adjustment characteristics [at Q = 0 l/min (static)]



Q_{st+L} = f (p_{red}) Pilot- and leakage volume flow characteristic [A (1) → T (3)]



DIMENSIONS / SECTIONAL DRAWINGS



Dimensions of the other connection versions see data sheet 1.1-173

Cavity drawing acc. to
to Wandfluh standard



For detailed cavity drawing
see data sheet 2.13-1045

PARTS LIST

Position	Article	Description
10		EN 175301
	206.2201	Solenoid coil WD37/19x50-G24
	206.2200	Solenoid coil WD37/19x50-G12
		Junior-Timer
	206.2203	Solenoid coil WJ37/19x50-G24
	206.2202	Solenoid coil WJ37/19x50-G12
		Deutsch
	206.2205	Solenoid coil WG37/19x50-G24
	206.2204	Solenoid coil WG37/19x50-G12
15	253.8000	HB 4,5 Manual override (data sheet 1.1-300)
	239.2033	HB 0 Plug screw (data sheet 1.1-300)
20	154.2700	Knurled nut
30	160.6187	O-ring ID 18,72x2,62 (FKM)
40	160.6172	O-ring ID 17,17x1,78 (FKM)
50	160.2188	O-ring ID 18,77x1,78 (NBR)
	160.6188	O-ring ID 18,77x1,78 (FKM)
60	160.2156	O-ring ID 15,60x1,78 (NBR)
	160.6156	O-ring ID 15,60x1,78 (FKM)
70	160.2140	O-ring ID 14,00x1,78 (NBR)
	160.6141	O-ring ID 14,00x1,78 (FKM)
80	049.3196	Backup ring RD 16,1x19x1,4
90	049.3176	Backup ring RD 14,1x17x1,4

ACCESSORIES

Proportional amplifier — register 1.13
Mating connector EN 175301-803 — Article no. 219.2002

Technical explanation see data sheet 1.0-100